



## AXIS <mark>3</mark>.1

Length	325 cm / 10'7"		
Beam	181 cm / 5'11"		
Weight	210 kg / 462 lbs		
Fuel Tank	33 lt / 8.7 gal		
Tube Diameter	0.40 m / 15.7"		
Tube Pressure	0.18 bar / 2.6 psi		
Air Chambers	3		
Max Payload	4 pax		
Min HP	20 HP		
Recommended HP	25 HP		
Max HP	30 HP		
Shaft Length	S / L		
Design Category	CE - Cat C		

### AXIS <mark>3</mark>4

Length	340 cm / 11'2"		
Beam	175 cm / 5'9"		
Weight	210 kg / 462 lbs		
Fuel Tank	33 lt / 8.7 gal		
Tube Diameter	0.41 m / 16.1"		
Tube Pressure	0.18 bar / 2.6 psi		
Air Chambers	3		
Max Payload	4 pax		
Min HP	25 HP		
Recommended HP	30 HP		
Max HP	40 HP		
Shaft Length	L		
Design Category	CE - Cat C		

## AXIS <mark>3</mark>.8

Length	385 cm / 12'6"		
Beam	191 cm / 6'3"		
Weight	245 kg / 540 lbs		
Fuel Tank	33 lt / 8.7 gal		
Tube Diameter	0.43 m / 16.9"		
Tube Pressure	0.18 bar / 2.6 psi		
Air Chambers	3		
Max Payload	5 pax		
Min HP	30 HP		
Recommended HP	40 HP		
Max HP	50 HP		
Shaft Length	L		
Design Category	CE - Cat C		

## AXIS **4**.2

Length	425 cm	1	13'9"
Beam	196 cm	1	6'5"
Weight	282 kg	1	621 I
Fuel Tank	42 lt	1	11.1
Tube Diameter	0.43 m	1	16.9
Tube Pressure	0.18 bar	1	2.6 p
Air Chambers		4	-
Max Payload		6 p	ax
Min HP		10 I	
Recommended HP	1	50 I	ΗP
Max HP	(	50 I	ΗP
Shaft Length		L	-
Design Category	CE	- C	at C

## minimalist design with maximalist features

- 🔥 Delta-lift<sup>®</sup> hull; offering easy planing with integrated Delta tabs aft
- B Replaceable transoms
- Standard hydraulic steering
- D Ergonomic consoles
- Sturdy acrylic glove box for loose items
  USB charging port and main cut off switch inside
- **F** Standard fuel system with integral fuel tank, fuel gauge and water separator
- G Standard electrical system with the following: Switch panel

  - LED navigation lights
    All-round light (socket type)
  - Automatic bilge pump
- B Self-bailing deck
- Large storage areas
- Marine upholstery
- K Sturdy Hypalon (CSM) tubes
- Standard Swimming ladder Pop up cleats (3 pcs) Lifting rings (4 pcs)
   Towing rings (3 pcs U-bolt)

# AXIS <mark>4</mark>.8

ength	485 cm / 15'9"		
Beam	223 cm / 7'3"		
Veight	420 kg / 925 lbs		
uel Tank	51 lt / 13.5 gal		
ube Diameter	0.46 m / 18.1"		
ube Pressure	0.18 bar / 2.6 psi		
Vir Chambers	4		
/lax Payload	8 pax		
/in HP	50 HP		
Recommended HP	70 HP		
Aax HP	80 HP		
haft Length	L		
Design Category	CE - Cat C		

### AXIS <u>5</u>.3

Length	535 cm / 17'5"	
Beam	233 cm / 7'8"	
Weight	495 kg / 1091 lbs	
Fuel Tank	62 lt / 16.4 gal	
Tube Diameter	0.48 m / 18.9"	
Tube Pressure	0.18 bar / 2.6 psi	
Air Chambers	4	
Max Payload	9 pax	
Min HP	70 HP	
Recommended HP	90 HP	
Max HP	115 HP	
Shaft Length	L	
Design Category	CE - Cat C	

# all with the traditional Northstar qulity



ß





Northstar AXIS Tenders have been developed to answer all the critical needs for a functional, ergonomic and performing yacht tender. AXIS Tenders are offered in 6 different lengths between 3.2m (10'7") and 5.3 (17'5") to fit a variety of swimming platforms and garages. Benefiting from the Delta-lift hull shape with integrated delta tabs aft, all AXIS tenders plane very easily and ride dry.

Fitted with standard features like hydraulic steering, CSM (Hypalon) tubes, built-in fuel tank, pop-up cleats, extensive electrical system with auto bilge pump, navigation lights and USB charging socket, an AXIS tender is ready to become your indispensable tool around your yacht.









LED floor lighting

EVA Faux teak deck



Pop up ski tow pylon (4.2 / 4.8 / 5.3)





Console railing (4.2 / 4.8 / 5.3)

Additional seat (4.2 / 4.8 / 5.3)

Bimini Top (4.2 / 4.8 / 5.3)







